Magnetized Beam on Viewers

Abdullah Mamun June 26, 2017


Magnetized Beams on Viewers


- Magnetic field on the gun solenoid was varied with solenoid current ranging from 0-400 A.
- Two sets of data were collected as:
 - Case 1: beamline lenses were all turned off
 - Case 2: used lens 2 for beam waist immediately prior to viewer 1. All other beamline lenses were turned off.


Measurement of Rotation Angles

- The slit images on different viewers were analyzed to determine the slope with respect to x (+ve) axis using the linear least square fit method.
- Sign convention used:
 - a clockwise rotation w.r.t. x-axis is +ve angle
 - a counter clockwise w.r.t. x-axis is -ve angle


Example of Rotation Measurement








Rotation from Slit-Viewer Images




Rotation from Slit-Viewer Images



The modified data after forcing to match the expected zero rotation at 0 A gun solenoid setting.


Rotation Angles from Diverging Beam



Contrary to expectation, the beamlet images on viewers depicted non trivial rotation (4.2° to 8.1°) at 0 A gun solenoid setting. How a focusing lens can impart angular momentum!

Rotation Angles from Diverging Beam

Rotation vs. B (Case 2, Rotation zeroed for 0A gun solenoid current)



The modified data after forcing to match the expected zero rotation at 0 A gun solenoid setting.

Summary


- Two sets of beam rotation measurement were performed- (1) without use of any beamline forcing lenses, and (2) with forcing the beam to focus prior to viewer 1 using beamline lens#2
- Case 1 showed oscillatory pattern in rotation
- Case 2 results are ambiguous and not clear why there appeared beamlet rotation by focusing lens for nonmagnetized beam
- The angular momentum will be analyzed later


Experimental Data


BEAM AND BEAMLET IMAGES


Magnetized Beam on Viewers


(case 1: beamline lenses were all turned off)







































































































































































Magnetized Beam on Viewers

(case 2: used lens 2 for beam waist immediately prior to viewer 1)

