

Mott Run Time Estimates

- DAQ rate < 5,000 Hz
- Beam current < 50 μA
- Target thickness extrapolation from Steigerwald is included
- Dump events: 25 Hz/ μA per detector
- Beam polarization: 85%
- Statistical error ($\delta p/p$): 0.5%

Au Target - 3.0 MeV

Target Thickness (μm)	I (μA)	Time (hr)	DAQ Rate (Hz)	Asym (%)	S_{eff}
0.05	12.76	0.04	5000	-40.49	-0.4763
0.10	7.31	0.03	5000	-40.16	-0.4725
0.35	2.33	0.03	5000	-38.62	-0.4543
1.0	0.84	0.04	5000	-35.11	-0.4130
5.0	0.17	0.09	5000	-22.51	-0.2649

Au Target - 5.0 MeV

Target Thickness (μm)	I (μA)	Time (hr)	DAQ Rate (Hz)	Asym (%)	S_{eff}
0.05	29.77	0.06	5000	-43.77	-0.5150
0.10	21.19	0.04	5000	-43.20	-0.5083
0.35	8.69	0.03	5000	-40.57	-0.4773
1.0	3.43	0.04	5000	-35.02	-0.4120
5.0	0.73	0.12	5000	-19.01	-0.2237

Au Target - 8.0 MeV

Target Thickness (μm)	I (μA)	Time (hr)	DAQ Rate (Hz)	Asym (%)	S_{eff}
0.05	41.54	0.17	5000	-38.98	-0.4586
0.10	35.52	0.11	5000	-38.19	-0.4493
0.35	20.61	0.06	5000	-34.68	-0.4080
1.0	9.85	0.07	5000	-27.98	-0.3292
5.0	2.34	0.29	5000	-12.79	-0.1504

Ag Target - 5.0 MeV

Target Thickness (μm)	I (μA)	Time (hr)	DAQ Rate (Hz)	Asym (%)	S_{eff}
0.05	45.18	0.95	5000	-22.02	-0.2591
0.10	41.20	0.53	5000	-21.74	-0.2557
0.35	28.62	0.25	5000	-20.41	-0.2401
1.0	15.95	0.21	5000	-17.62	-0.2073
5.0	4.28	0.53	5000	-9.57	-0.1125

Cu Target - 5.0 MeV

Target Thickness (μm)	I (μA)	Time (hr)	DAQ Rate (Hz)	Asym (%)	S_{eff}
0.05	47.87	7.82	5000	-11.55	-0.1359
0.10	45.92	4.18	5000	-11.40	-0.13.42
0.35	38.13	1.63	5000	-10.71	-0.1260
1.0	26.46	1.11	5000	-9.24	-0.1087
5.0	9.18	2.16	5000	-5.02	-0.0590