

Error Analysis I

04 September 2013

Penfold-Leiss Cross Section Unfolding

- Measure Yields at: $E = E_1, E_2, \dots, E_n$ where,
 $E_i - E_{i-1} = \Delta, i = 2, n$

$$Y(E_i) = \int_{th}^{E_i} n_\gamma(E_i, k) \sigma(k) dk \approx \sum_{j=1}^i N_\gamma(E_i, \Delta, E_j) \sigma(E_j)$$

- The solution can be written in two forms:

$$\sigma_i = \frac{1}{N_{ii}} \left[y_i - \sum_{j=1}^{i-1} (N_{ij} \sigma_j) \right]$$

- Or, Matrix form:

$$\begin{bmatrix} y_1 \\ y_2 \\ \vdots \\ y_n \end{bmatrix} = \begin{bmatrix} N_{\gamma,11} & 0 & \cdots & 0 \\ N_{\gamma,21} & N_{\gamma,22} & \cdots & 0 \\ \vdots & \ddots & \ddots & 0 \\ N_{\gamma,n1} & N_{\gamma,n2} & \cdots & N_{\gamma,nn} \end{bmatrix} \begin{bmatrix} \sigma_1 \\ \sigma_2 \\ \vdots \\ \sigma_n \end{bmatrix}$$

$$[Y] = [N] \bullet [\sigma]$$

$$[\sigma] = [N]^{-1} \bullet [Y]$$

Statistical Error

Statistical Error Propagation (1)

- Note: $\frac{dy_i}{y_i} = \frac{1}{\sqrt{y_i}}$ $\frac{dN_{ij}}{N_{ij}} = \frac{1}{\sqrt{N_{ij}}} \approx 0$

$$dy_i = \sqrt{y_i}$$

$$dy_i = \sqrt{y_i + 2y_i^{bg}}$$

In case of
background
Subtraction

- With:

$$[B] = [N]^{-1}$$

$$[\sigma] = [B] \bullet [Y]$$

- Then:

$$[d\sigma^2] = [B] \bullet [dY^2] \bullet [B]^T$$

- Where:

$$[dY^2] = \begin{bmatrix} y_1 & 0 & \cdots & 0 \\ 0 & y_2 & \cdots & 0 \\ \vdots & \ddots & \ddots & \vdots \\ 0 & 0 & \cdots & y_n \end{bmatrix}$$

$\text{var}(y_i, y_i) = y_i$
 $\text{cov}(y_i, y_j) = 0$

$$[d\sigma^2] = \begin{bmatrix} d\sigma_1^2 & \text{cov}(\sigma_1, \sigma_2) & \cdots & \text{cov}(\sigma_1, \sigma_n) \\ \text{cov}(\sigma_2, \sigma_1) & d\sigma_2^2 & \cdots & \text{cov}(\sigma_2, \sigma_n) \\ \vdots & \ddots & \ddots & \vdots \\ \text{cov}(\sigma_n, \sigma_1) & \text{cov}(\sigma_n, \sigma_2) & \cdots & d\sigma_n^2 \end{bmatrix}$$

Statistical Error Propagation (2)

$$(d\sigma_i)^2 = \frac{1}{N_{ii}^2} \left[dy_i^2 + \sum_{j=1}^{i-1} (N_{ij} d\sigma_j)^2 + \sum_{k=1}^{i-1} \sum_{l=1}^{i-1} N_{ik} \text{cov}(\sigma_k, \sigma_l) N_{il} \right]$$

Although,
 $\text{cov}(y_i, y_j) = 0$,
 $\text{cov}(\sigma_i, \sigma_j) \neq 0$

For mono-chromatic beam

$$\left(\frac{d\sigma_i}{\sigma_i} \right)^2 = \left(\frac{dy_i}{y_i} \right)^2 = \frac{1}{y_i}$$

Statistical Error Propagation (Wrong)

$$[\sigma] = [N]^{-1} \bullet [Y]$$

- Then:

Wrong

$$[d\sigma^2] = [N^2]^{-1} \bullet [dY^2]$$

- This is equivalent to:

$$(d\sigma_i)^2 = \frac{1}{N_{ii}^2} \left[dy_i^2 - \sum_{j=1}^{i-1} (N_{ij} d\sigma_j)^2 \right]$$

Wrong

Systematic Error

Systematic Error Propagation (1)

- For absolute beam energy uncertainty of δE ($= 0.1\%$):

$$\frac{dy_i}{y_i} = \frac{y_i(E_i + \delta E) - y_i(E_i)}{y_i(E_i)}$$

$$\frac{dN_{ij}}{N_{ij}} = \frac{N_{ij}(E_i + \delta E) - N_{ij}(E_i)}{N_{ij}(E_i)}$$

E_i (MeV)	dy_i/y_i (%)	$d\sigma_i/\sigma_i$ (%)
7.9	17.4	12.6
8.0	12.3	10.5
8.1	10.0	9.1
8.2	8.6	7.1
8.3	7.6	6.3
8.4	6.8	5.8
8.5	6.1	5.2

This is the cross section dependence on energy

- Accounted for dN_{ij} due to energy error when calculating dy_i

$$\approx \frac{\delta E}{i\Delta}$$

$$[dN_{ij} / N_{ij}] = \begin{bmatrix} 0.100 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0.058 & 0.050 & 0 & 0 & 0 & 0 & 0 \\ 0.041 & 0.039 & 0.033 & 0 & 0 & 0 & 0 \\ 0.031 & 0.031 & 0.029 & 0.025 & 0 & 0 & 0 \\ 0.025 & 0.025 & 0.025 & 0.023 & 0.020 & 0 & 0 \\ 0.021 & 0.021 & 0.021 & 0.021 & 0.020 & 0.017 & 0 \\ 0.018 & 0.018 & 0.018 & 0.018 & 0.018 & 0.017 & 0.022 \end{bmatrix}$$

- With:

$$[B] = [N]^{-1}$$

$$[\sigma] = [B] \bullet [Y]$$

- Then:

$$[d\sigma^2] = [B] \bullet ([dY^2] + [dN^2] \bullet [\sigma^2]) \bullet [B]^T$$

- Where:

$$[dN^2] = \begin{bmatrix} (dN_{11})^2 & 0 & \cdots & 0 \\ (dN_{21})^2 & (dN_{22})^2 & \cdots & 0 \\ \vdots & \ddots & \ddots & \vdots \\ (dN_{n1})^2 & (dN_{n2})^2 & \cdots & (dN_{nn})^2 \end{bmatrix}$$

$$[dY^2] = \begin{bmatrix} (dy_1)^2 & 0 & \cdots & 0 \\ 0 & (dy_2)^2 & \cdots & 0 \\ \vdots & \ddots & \ddots & \vdots \\ 0 & 0 & \cdots & (dy_n)^2 \end{bmatrix} \quad [\sigma^2] = \begin{bmatrix} \sigma_1^2 & 0 & \cdots & 0 \\ 0 & \sigma_2^2 & \cdots & 0 \\ \vdots & \ddots & \ddots & \vdots \\ 0 & 0 & \cdots & \sigma_n^2 \end{bmatrix}$$

Systematic Error Propagation (2)

$$(d\sigma_i)^2 = \frac{1}{N_{ii}^2} \left[dy_i^2 + \sum_{j=1}^{i-1} (N_{ij} d\sigma_j)^2 + \sum_{k=1}^{i-1} \sum_{l=1}^{i-1} N_{ik} \text{cov}(\sigma_k, \sigma_l) N_{il} \right. \\ \left. + \sum_{j=1}^{i-1} (dN_{ij} \sigma_j)^2 + (dN_{ii} d\sigma_i)^2 \right]$$

Other Systematic Errors

Beam Current, $\delta I/I$	3%
Photon Flux, $\delta\phi/\phi$	5%
Radiator Thickness, $\delta R/R$	3%
Bubble Chamber Thickness, $\delta T/T$	3%
Bubble Chamber Efficiency, ε	5%

Simulation

- Then:

$$(dy_i)^2 = (dy_i(\delta E))^2 + \left[\left(\frac{\delta I}{I} \right)^2 + \left(\frac{\delta R}{R} \right)^2 + \left(\frac{\delta T}{T} \right)^2 + \varepsilon^2 \right] y_i^2$$

$$(dN_{ij})^2 = \left(\frac{\delta \phi}{\phi} \right)^2 N_{ij}^2$$

Results

- I. Radiator Thickness = 0.02 mm
- II. Bubble Chamber Thickness = 3.0 cm
- III. Number of ^{16}O nuclei = 3.474e22 /cm 2
- IV. Background subtraction of $^{18}\text{O}(\gamma,\alpha)^{14}\text{C}$
- V. $^{17}\text{O}(\gamma,n)^{16}\text{O}$: Still to do

Electron Beam K. E.	Beam Current (μA)	Time (hour)	y_i	dy_i (no bg)	dy_i/y_i (no bg, %)	dy_i (with bg)	dy_i/y_i (with bg, %)
7.9	100	100	545	23	4.2	134	24.6
8.0	100	20	581	24	4.1	77	13.3
8.1	80	10	852	29	3.4	60	7.0
8.2	20	10	634	25	3.9	40	6.3
8.3	10	10	812	28	3.4	39	4.8
8.4	4	10	746	27	3.6	36	4.8
8.5	2	10	763	28	3.7	32	4.2

$$[N] = \begin{bmatrix} 3.267e14 & 0 & 0 & 0 & 0 & 0 & 0 \\ 9.782e13 & 6.439e13 & 0 & 0 & 0 & 0 & 0 \\ 5.013e13 & 3.858e13 & 2.539e13 & 0 & 0 & 0 & 0 \\ 1.494e13 & 1.236e13 & 9.514e12 & 6.258e12 & 0 & 0 & 0 \\ 8.540e12 & 7.369e12 & 6.097e12 & 4.692e12 & 3.086e12 & 0 & 0 \\ 3.801e12 & 3.370e12 & 2.908e12 & 2.406e12 & 1.852e12 & 1.217e12 & 0 \\ 2.075e12 & 1.875e12 & 1.663e12 & 1.435e12 & 1.187e12 & 9.137e11 & 6.004e11 \end{bmatrix}$$

Electron Beam K. E.	Cross Section (nb)	Stat Error (no bg, %)	Stat Error (with bg, %)
7.9	0.046	4.4	24.5
8.0	0.185	6.0	20.7
8.1	0.58	6.3	14.7
8.2	1.53	8.2	13.8
8.3	3.49	9.1	13.3
8.4	7.2	10.6	13.8
8.5	13.6	12.2	14.8

Electron Beam K. E.	Cross Section (nb)	Sys Error (Energy, %)	Sys Error (Total, %)
7.9	0.046	17.4	19.5
8.0	0.185	18.1	21.5
8.1	0.58	18.4	22.9
8.2	1.53	18.9	24.9
8.3	3.49	19.7	27.2
8.4	7.2	20.6	30.0
8.5	13.6	21.6	33.0

Electron Beam K. E.	Gamma Energy (MeV)	E_{CM} (MeV)	Cross Section (nb)	S_{E1} Factor (keV b)	Stat Error (%)	Sys Error (%)
7.9	7.85	0.69	0.046	62.2	24.5	19.5
8.0	7.95	0.79	0.185	48.7	20.7	21.5
8.1	8.05	0.89	0.58	41.8	14.7	22.8
8.2	8.15	0.99	1.53	35.5	13.8	24.9
8.3	8.25	1.09	3.49	32.0	13.3	27.2
8.4	8.35	1.19	7.2	28.8	13.8	30.0
8.5	8.45	1.29	13.6	26.3	14.8	33.0

$^{12}\text{C}(\alpha, \gamma)^{16}\text{O}$ S-Factor

- Statistical Error: dominated by background subtraction from $^{18}\text{O}(\gamma, \alpha)^{14}\text{C}$ (depletion = 5,000)
- Systematic Error: dominated by absolute beam energy ($\delta E = 0.1\%$)

