Radiation hardnes measurements of PbWO4 crystals at IPN-Orsay

Ho San KO
PHEN Institut de Physique Nucléaire d'Orsay
17. May. 2018

Outline

- Orsay irradiation Facility
  -Fricke dosimetry to measure the gamma dose and dose rate
  -PbWO4 Irradiation

- PbWO4 transmittance and dK results comparisons with Giessen’s

Irradiation Facility





- Co60 source, 222TBq
- With simple mechanical design, the distance from the source can be reproduced.
- With this setup, we can irradiate 9 crystals/water at the same time.
- Bottom figure is to irradiate with higher dose rate.

(15cm from the source)

- Results to be shown today were irradiated 60cm from the source

Irradiation Facility

- To estimate the dose and dose rate in crystals

-We irradiated water(Fricke solution) with the same positions(distance from the gamma source) and the same shape and volume of those of the crystals.



-Fricke dosimetry is well studied. It changes the light absorption linearly by the irradiation at certain wavelength until certain amount of dose(~200Gy).

Fricke solution

$$H + O_2 \rightarrow HO_2$$

$$Fe^{2+} + HO_2 \rightarrow Fe^{3+} + HO_2^-$$

$$HO_2^- + H^+ \rightarrow H_2O_2$$

$$Fe^{2+} + H_2O_2 \rightarrow Fe^{3+} + OH + OH^-$$

$$Fe^{2+} + OH \rightarrow Fe^{3+} + OH^-$$

- Solution of Fe2+
- Gamma irradiates water -> Ferrous ions(Fe2+) to Ferric ions(Fe3+)
- Fe3+ absorbs light. Peak at 304nm

Water Irradiation Results



60cm away from the source

- Light absorption increases with respect to the dose.
- Get the peak values at 304nm to get the absorption change rate

Water Irradiation Results

- Absorbance changes throughout irradiation.



60cm away from the source

- Increase of light absorption throughout irradiation time

- With the absorption change rate, we can get the dose rate.

Water Irradiation Results

- Dose rate calculation from solution's absorbance

$$\text{Absorbance } (A) = log\frac{I_0}{I} = \varepsilon \times l \times C = \varepsilon \times l \times G \times \rho \times D(t)$$

$$\text{Dose rate}(Gy/min) = \frac{\Delta A(cm^{-1})}{\varepsilon(L\ mol^{-1}) \times G(mol\ J^{-1}) \times \rho(kg\ L^{-1})} \times \frac{1}{\Delta t(min)}$$

I : measured light intensity through the material

ε : molar extinction coefficient. 2160 + 15(T - 25) at 304nm

l : optical path

C : number of moles transformed by the irradiation

G : efficiency for appearance of Fe3+ 1.62 X 10-7 mole/J

ρ : mass density of the solution

$D(t)$: radiation dose

Water Irradiation Results



- Dose rate average of 1.11Gy/min (Giessen's : 1.16Gy/min)

PbWO4 Irradiation Results

- Crystals' color changes after irradiation.



- The picture was taken after higher dose rate(>17Gy/min)

PbWO4 Irradiation Results

- Crystals’ color changes after irradiation.



J11 J23, damaged the most J15, non-irradiated

- The picture was taken after higher dose rate(>17Gy/min)

PbWO4 Irradiation Results

J11



J33



J38



J34



J43



J23



J44



J37



J31



PbWO4 Irradiation Results

- Delta K $dk = ln(T_b/T_a)/l$ dK limit used for PANDA : 1.1/m



















Summary

- Using water irradiation, we can measure the dose rate.
  -Try irradiation damage tests with higher dose rate by changing the distance from the radiation source.

- IPN’s & Giessens’ transmittance & dK results are in very good agreement.

- Upcoming curing system test

Backups

IPN Radiation Facility

- Dose rate calculation from solution's absorbance

$$\text{Absorbance } (A) = log\frac{I_0}{I} = \varepsilon \times l \times C = \varepsilon \times l \times G \times \rho \times D(t)$$

$$\text{Dose rate}(Gy/min) = \frac{\Delta A(cm^{-1})}{\varepsilon(L\ mol^{-1}) \times G(mol\ J^{-1}) \times \rho(kg\ L^{-1})} \times \frac{1}{\Delta t(min)}$$

I : measured light intensity through the material

ε : molar extinction coefficient. 2160 + 15(T - 25) at 304nm

l : optical path

C : number of moles transformed by the irradiation

G : efficiency for appearance of Fe3+ 1.62 X 10-7 mole/J

ρ : mass density of the solution

$D(t)$: radiation dose

IPN Radiation Facility

- Dose rate calculation from solution's absorbance

$$\text{Absorbance } (A) = log\frac{I_0}{I} = \varepsilon \times l \times C = \varepsilon \times l \times G \times \rho \times D(t)$$

I : measured light intensity through the material

ε : molar extinction coefficient. 2160 + 15(T - 25) at 304nm

l : optical path

C : number of moles transformed by the irradiation

G : efficiency for appearance of Fe3+ 1.62 X 10-7 mole/J

ρ : mass density of the solution

$D(t)$: radiation dose

IPN Radiation Facility

- Dose rate calculation from solution's absorbance

$$\text{Dose rate}(Gy/min) = \frac{\Delta A(cm^{-1})}{\varepsilon(L\ mol^{-1}) \times G(mol\ J^{-1}) \times \rho(kg\ L^{-1})} \times \frac{1}{\Delta t(min)}$$

ε : molar absorption coefficient. 2160 + 15(T - 25) at 304nm

ρ : mass density of the solution

G : efficiency for appearance of Fe3+ 1.62 X 10-7 mole/J

Water Irradiation Results



















Light absorption increases with respect to the dose.
Peak at 304nm

Water Irradiation Results

Slopes, Cell No.3



Slopes, Cell No.6



Slopes, Cell No.9



Slopes, Cell No.2



Slopes, Cell No.5



Slopes, Cell No.8



Slopes, Cell No.1



Slopes, Cell No.4



Slopes, Cell No.7



- Plots of the absorbance value at 304nm throughout time.

Water Irradiation Results



Plots of the absorbance value at 304nm throughout time.

Water Irradiation Results



Plots of the absorbance value at 304nm throughout time.

Crystal Irradiation Results

J11



J23



J31



J33



J34



J37



J38



J43



J44



Crystal Irradiation Results



















Plots of the absorbance value at 304nm throughout time.

Crystal Irradiation Results

J11



J23



J31



J33



J34



J37



J38



J43



J44



Crystal Irradiation Results