

Project: PS-TGT-12-001 Hall A Tritium Target

Title: Beam energy loss in the target

Document Number: TGT-CALC-103-003

Revision: Rev 1

Author: Dave Meekins

Date: 8/13/2015

Code(s) of Record:

Reference:

Leo: Techniques for Nuclear and Particle Physics

Description:

General calculations for beam energy loss in the T2 target cell and Be isolation window. Calc follows Bethe-Bloch with simplified parameterization of density effect instead of full Sternheimer's. Only electron collision energy loss is considered.

Loss is considered for aluminum windows and T2 gas.

Reference Drawing(s):

TGT-103-1000-0012 Cell assy

Units and constants:

$$eV := 1.602 \cdot 10^{-19} \cdot J$$

$$MeV := 10^6 \cdot eV$$

$$r_e := 2.817 \cdot 10^{-13} \cdot cm$$

classical radius of electron

Collision energy loss of electron beam on target material. The method is from Leo. The shell correction is neglected.

Beam properties:

$$I_{beam} := 20 \cdot \mu A$$

beam current

$$m_e := 0.511 \cdot \frac{MeV}{c^2}$$

electron rest mass

$$E_e := 11000 \cdot MeV$$

Beam energy

$$\tau := \frac{E_e - m_e \cdot c^2}{m_e \cdot c^2} = 2.153 \cdot 10^4$$

kinetic energy of e- in units
of $m_e c^2$

$$P_e := \frac{1}{c} \cdot \sqrt{E_e^2 - (m_e \cdot c^2)^2}$$

momentum of e-

$$v_e := \sqrt{\frac{P_e^2}{m_e^2 + \frac{P_e^2}{c^2}}}$$

velocity of e-

$$\beta := \frac{v_e}{c}$$

beta

$$\gamma := \frac{1}{\sqrt{1 - \beta^2}}$$

gamma

$$X := \log(\beta \cdot \gamma) = 4.333$$

$$\eta := \beta \cdot \gamma = 2.153 \cdot 10^4$$

Aluminum entrance window

7075 aluminum is treated as pure aluminum for this calculation with the higher density of 7075.

$$L_x := 0.010 \cdot \text{in} = 0.254 \text{ mm}$$

length of absorber material

$$Z := 13$$

Atomic number

$$A := 26.98 \cdot \frac{\text{gm}}{\text{mol}}$$

Atomic weight

$$\rho := 2.69 \cdot \frac{\text{gm}}{\text{cm}^3}$$

density

$$I := \text{if } Z < 13$$

$$\quad \quad \quad \parallel (12 \cdot Z + 7) \cdot \text{eV}$$

Ionization potential

else

$$\quad \quad \quad \parallel (9.76 \cdot Z + 58.8 \cdot Z^{-0.19}) \cdot \text{eV}$$

$$hv_p := 28.816 \cdot \sqrt{\frac{\rho \cdot Z}{A}} \cdot \text{eV} \cdot \sqrt{\frac{\text{cm}^3}{\text{mol}}} = 32.807 \text{ eV}$$

plasma energy

$$C_1 := - \left(2 \cdot \ln \left(\frac{I}{hv_p} \right) + 1 \right) = -4.206$$

$$\delta := \text{if } X < 3$$

$$\quad \quad \quad \parallel 4.6052 \cdot X + C_1 + \frac{C_1}{27} \cdot (3 - X)^3$$

else

$$\quad \quad \quad \parallel 4.6052 \cdot X + C_1$$

$$F_t := 1 - \beta^2 + \frac{\frac{\tau^2}{8} - (2 \cdot \tau + 1) \cdot \ln(2)}{(\tau + 1)^2}$$

first function of τ

$$dE := -2 \cdot \pi \cdot N_A \cdot r_e^2 \cdot m_e \cdot c^2 \cdot \rho \cdot \frac{Z}{A} \cdot \frac{1}{\beta^2} \cdot \left(\ln \left(\tau^2 \cdot \frac{(\tau+2)}{2 \left(\frac{I}{m_e \cdot c^2} \right)^2} \right) + F_t - \delta + 0.6 \right)$$

$$Q_{ent} := dE \cdot L_x \cdot \frac{I_{beam}}{e_c} = -3.062 \text{ W}$$

Aluminum exit window

7075 aluminum is treated as pure aluminum for this calculation

Properties of the absorbing material

$$L_x := 0.011 \cdot \text{in} = 0.279 \text{ mm}$$

length of absorber material

$$Z := 13$$

Atomic number

$$A := 26.98 \cdot \frac{\text{gm}}{\text{mol}}$$

Atomic weight

$$\rho := 2.69 \cdot \frac{\text{gm}}{\text{cm}^3}$$

density

$$I := \text{if } Z < 13$$

$$\quad \quad \quad \parallel (12 \cdot Z + 7) \cdot \text{eV}$$

Ionization potential

else

$$\quad \quad \quad \parallel (9.76 \cdot Z + 58.8 \cdot Z^{-0.19}) \cdot \text{eV}$$

$$hv_p := 28.816 \cdot \sqrt{\frac{\rho \cdot Z}{A}} \cdot \text{eV} \cdot \sqrt{\frac{\text{cm}^3}{\text{mol}}} = 32.807 \text{ eV}$$

plasma energy

$$C_1 := - \left(2 \cdot \ln \left(\frac{I}{hv_p} \right) + 1 \right) = -4.206$$

constant

$$\delta := \text{if } X < 3$$

$$\quad \quad \quad \parallel 4.6052 \cdot X + C_1 + \frac{C_1}{27} \cdot (3 - X)^3$$

else

$$\quad \quad \quad \parallel 4.6052 \cdot X + C_1$$

$$F_t := 1 - \beta^2 + \frac{\frac{\tau^2}{8} - (2 \cdot \tau + 1) \cdot \ln(2)}{(\tau + 1)^2}$$

first function of τ

$$dE := -2 \cdot \pi \cdot N_A \cdot r_e^2 \cdot m_e \cdot c^2 \cdot \rho \cdot \frac{Z}{A} \cdot \frac{1}{\beta^2} \cdot \left\{ \ln \left(\tau^2 \cdot \frac{(\tau+2)}{2 \left(\frac{I}{m_e \cdot c^2} \right)^2} \right) + F_t - \delta \right\}$$

$$dE \cdot L_x = -0.165 \text{ MeV}$$

$$Q_{exit} := dE \cdot L_x \cdot \frac{I_{beam}}{e_c} = -3.302 \text{ W}$$

Energy loss in the T2 gas. Average density of the gas is considered. local variations along path are ignored. Properties of the absorbing material

$$L_x := 250 \cdot \text{mm}$$

length of absorber material

$$Z := 1$$

Atomic number

$$A := 3 \cdot \frac{\text{gm}}{\text{mol}}$$

Atomic weight

$$\rho := 0.003 \cdot \frac{\text{gm}}{\text{cm}^3}$$

density

$$I := \text{if } Z < 13$$

$$\quad \quad \quad \parallel (12 \cdot Z + 7) \cdot \text{eV}$$

Ionization potential

else

$$\quad \quad \quad \parallel (9.76 \cdot Z + 58.8 \cdot Z^{-0.19}) \cdot \text{eV}$$

$$hv_p := 28.816 \cdot \sqrt{\frac{\rho \cdot Z}{A}} \cdot \text{eV} \cdot \sqrt{\frac{\text{cm}^3}{\text{mol}}} = 0.911 \text{ eV}$$

plasma energy

$$C_1 := - \left(2 \cdot \ln \left(\frac{I}{hv_p} \right) + 1 \right) = -7.075$$

constant

$$\delta := \text{if } X < 3$$

$$\quad \quad \quad \parallel 4.6052 \cdot X + C_1 + \frac{C_1}{27} \cdot (3 - X)^3$$

else

$$\quad \quad \quad \parallel 4.6052 \cdot X + C_1$$

$$F_t := 1 - \beta^2 + \frac{\frac{\tau^2}{8} - (2 \cdot \tau + 1) \cdot \ln(2)}{(\tau + 1)^2}$$

first function of τ

$$dE := -2 \cdot \pi \cdot N_A \cdot r_e^2 \cdot m_e \cdot c^2 \cdot \rho \cdot \frac{Z}{A} \cdot \frac{1}{\beta^2} \cdot \left(\ln \left(\tau^2 \cdot \frac{(\tau+2)}{2 \left(\frac{I}{m_e \cdot c^2} \right)^2} \right) + F_t - \delta \right)$$

$$dE \cdot L_x = -0.141 \text{ MeV}$$

$$Q_{T2} := dE \cdot L_x \cdot \frac{I_{beam}}{e_c} = -2.829 \text{ W}$$

Total energy lost in the target is then:

$$Q_{tot} := Q_{T2} + Q_{ent} + Q_{exit} = -9.194 \text{ W}$$

Energy Density:

For a 2x2 raster with $20 \mu A$ beam current the power density in the aluminum is

$$d_{raster} := 2 \cdot \text{mm}$$

raster leg size

$$A := d_{raster}^2$$

raster area

$$t := 0.01 \cdot \text{in}$$

thickness of entrance window

$$V := t \cdot A = (1.016 \cdot 10^{-9}) \text{ m}^3$$

Volume of material impacted by the beam

$$q := \frac{Q_{ent}}{V} = -3.014 \cdot 10^9 \frac{\text{W}}{\text{m}^3}$$

volumetric heat density from beam

This result is applicable to the exit window as well. It shall be used in the thermal FEA.

With no raster the beam is assumed to be $150 \mu m$ in diameter. While there are safeguards to prevent running in this condition, they take some time to implement. The power density for this case shall be used to model the raster off conditions for the cell.

$$d_{beam} := 0.150 \cdot \text{mm}$$

$$A_{beam} := \frac{\pi}{4} \cdot d_{beam}^2$$

$$V_{beam} := t \cdot A_{beam}$$

$$q_{beam} := \frac{Q_{ent}}{V_{beam}} = -6.823 \cdot 10^{11} \frac{\text{W}}{\text{m}^3}$$

In the target gas

$$d_{raster} := 2 \cdot \text{mm}$$

raster leg size

$$A := d_{raster}^2$$

raster area

$$t := 25 \cdot \text{cm}$$

thickness of entrance window

$$V := t \cdot A = (1 \cdot 10^{-6}) \text{ m}^3$$

Volume of material impacted by the beam

$$q := \frac{Q_{T2}}{V} = -2.829 \cdot 10^6 \frac{\text{W}}{\text{m}^3}$$

volumetric heat density from beam