

# LERF RF User Guide

---

*Last updated  
2/1/2019, 12:30 PST  
S. Hoobler*

## Contents

I.	Standard Controls and Information.....	2
1.	CPU's and IOCs .....	2
2.	Chassis IPs.....	2
3.	Start/Restart the EPICS IOC .....	2
4.	View RF EDM screens.....	4
5.	Initialize/Checkout LLRF Hardware .....	5
6.	View RF Waveform Plots.....	6
7.	Control Stepper Motor Tuner .....	8
8.	Control Piezo Tuner .....	9
9.	Drive Cavity With Simple Tone Signal .....	10
10.	Run RF In SEL Pulsed Mode .....	11
11.	Ramp Cavity to CW/SELAP and Perform Cavity Characterization.....	12
II.	Occasional Issues .....	13
1.	Mystery Rack Checkout Error .....	13
2.	Recover Non-Updating EPICS Waveforms .....	14
3.	Ping Test .....	15
4.	View the EPICS IOC Console .....	15
5.	Troubleshoot RFS<->Res/Intlk Communication .....	16
6.	RF 'Background Process' .....	18

# I. Standard Controls and Information

## 1. CPUs and IOCs

<i>JLab Cryomodule Number</i>	<i>LCLS-II Cryomodule Name</i>	<i>CPU Node Name*</i>	<i>EPICS IOC Name*</i>
1	ACCL:L1B:0200	lcls-llrfcpu01	sioc-l1b-rf01
2	ACCL:L1B:0300	lcls-llrfcpu02	sioc-l1b-rf02

*\*CPU Node Name is referred to as <cpuname>in the commands shown below.*

*EPICS IOC Name is referred to as <iocname> in the commands shown below.*

## 2. Chassis IPs

These are the IP addresses used in the LLRF internal network. They are the same for each cryomodule.

<i>Rack</i>	<i>Chassis</i>	<i>IP</i>
Cavities 1-4 (aka Rack A)	RES	192.168.0.100
Cavities 1-4 (aka Rack A)	RFS1 (cavities 1,2)	192.168.0.101
Cavities 1-4 (aka Rack A)	RFS2 (cavities 3,4)	192.168.0.102
Cavities 1-4 (aka Rack A)	PRC	192.168.0.103
Cavities 5-8 (aka Rack B)	RES	192.168.0.200
Cavities 5-8 (aka Rack B)	RFS1 (cavities 5,6)	192.168.0.201
Cavities 5-8 (aka Rack B)	RFS2 (cavities 7,8)	192.168.0.202
Cavities 5-8 (aka Rack B)	PRC	192.168.0.203

PRC=Precision Receiver Chassis

Reads cavity probe signals

RFS=RF Station


Provides RF drive; reads forward , reverse, detune signals

RES=Resonance/Interlock Chassis


Controls tuners; performs interlock logic

## 3. Start/Restart the EPICS IOC


1. Log into LERF workstation or server  
(lcls01/2/3/lclsapp1 with individual user id)
2. Type lerfhome&



3. Click on box intersecting Network and L1B




4. Click on IOC of interest




5. Click on 'Reboot'. Then click on 'Reboot Now!'

## 4. View RF EDM screens


- Log into LERF workstation or server (lcls01/2/3/lclsapp1 with individual user id)
- Type lerfhome&



- Click on box intersecting RF and L1B



L1B Overview Display




Single Cavity Display

## 5. Initialize/Checkout LLRF Hardware

Needed after power outage, hardware swap, etc.

- Click on Hardware... (from either L1B Overview or Single Cavity display—see above).





- For appropriate rack (A or B), open display labelled Rack Hardware Init and Test...

- Execute RFS/PRC initialization and checkout. Click Go  
(The script will disable and then re-enable communication with EPICS.)

To view the rack test script output, click on Log...


It will open an xterm window and display the script output as it progresses.





- d. Initialize RES chassis. Click Go  
(The script will disable and then re-enable communication with EPICS.)

## 6. View RF Waveform Plots







Cavity Overview -- Cavity, Forward, Reverse signals for single cavity


Cryomodule Overview -- Cavity, Forward, Reverse signals for all 8 cavities

More Cavity -- Drop-down menu for single-cavity single-signal screen


From those screens, you can navigate to other cavities, other signals, or display a single signal for all 8 cavities. Example screenshots:



## 7. Control Stepper Motor Tuner




a. Click on Stepper Tuner...




b. 8-cavity screen. From here you can enter number of steps and then click the green arrow to go in one direction or the other. (Relationship between direction and frequency is not yet known.) Click More... for single tuner screen



## 8. Control Piezo Tuner




a. Click on Piezo Tuner...



b. 8-cavity screen. From here you can enable the piezo tuner and enter a DC DAC voltage. Click More... for single piezo tuner screen

## 9. Drive Cavity With Simple Tone Signal




a. Click on Tone Test...



b. Turn desired cavity 'On', then enter number of DAC counts...


c. When done, click 'Off'

## 10. Run RF In SEL Pulsed Mode



a. Click on SEL Phase & Pulse...

The settings/options for pulsed mode are more complicated than you'd think. It's a good idea to read the README at the bottom of the screen.



b. Enter desired amplitude (settings will be 'yellow' if they do not match Current/Last In Use)

c. Enter desired RF pulse length


d. Click Go

e. When done, click Stop


f. To update amplitude or time settings, enter new values and then click Go again

## 11. Ramp Cavity to CW/SELAP and Perform Cavity Characterization

This is used to bring up a cavity 'from scratch' or if there is some need to re-characterize the cavity/SSA. You do not need to run this every time you turn a cavity on.



a. Click on Cavity Ramp-Up...




b. Set Amplitude Goal and click Go

c. Future (not yet done 1/29/2019): the script will write is calculated characterization parameters to the Newly Calculated values on the screen. You can review these and if they seem reasonable, click Push New Vals. You can also save the Current values as a known good set—to possibly restore in future.


## II. Occasional Issues

### 1. Mystery Rack Checkout Error

We occasionally see a problem during the first cryomodule rack A checkout. This is what it looks like:




```
[ ]
192.168.0.102
Write to /data/lcls-llrfcpu01/llrf/./live_prc_regmap.json
192.168.0.102
set_lims 0 0
Signal min/max 0/0, amplitude 0.0 0.0, rms error 0.00 OK
Signal min/max 0/0, amplitude 0.0 0.0, rms error 0.00 OK
crc_errors clk_status_out dac_iq_phase shell_0_dsp_use_fiber_iq [60179, 2, 1, 1]
set_lims 0 19750
Signal min/max -2032/2367, amplitude 2032.7 9.9, rms error 63.88 BAD
Signal min/max 0/0, amplitude 0.0 0.0, rms error 0.00 OK
crc_errors clk_status_out dac_iq_phase shell_0_dsp_use_fiber_iq [60179, 2, 1, 1]
set_lims 0 79000
Signal min/max -8150/8129, amplitude 8150.0 23.7, rms error 0.52 OK
Signal min/max 0/0, amplitude 0.0 0.0, rms error 0.00 OK
crc_errors clk_status_out dac_iq_phase shell_0_dsp_use_fiber_iq [60179, 2, 1, 1]
set_lims 1 19750
Signal min/max -2032/2032, amplitude 2032.1 5.9, rms error 0.49 OK
Signal min/max 0/0, amplitude 0.0 0.0, rms error 0.00 OK
crc_errors clk_status_out dac_iq_phase shell_1_dsp_use_fiber_iq [60179, 2, 1, 1]
set_lims 1 79000
Signal min/max -8150/8129, amplitude 8150.0 23.7, rms error 0.52 OK
Signal min/max 0/0, amplitude 0.0 0.0, rms error 0.00 OK
crc_errors clk_status_out dac_iq_phase shell_1_dsp_use_fiber_iq [60179, 2, 1, 1]
set_lims 0 0
Signal min/max 0/0, amplitude 0.0 0.0, rms error 0.00 OK
Signal min/max 0/0, amplitude 0.0 0.0, rms error 0.00 OK
crc_errors clk_status_out dac_iq_phase shell_0_dsp_use_fiber_iq [60179, 2, 1, 1]
FAIL
```



It is an intermittent failure and is not understood. You'll have to simply re-run rack checkout and hope it passes. (We have observed that if the system was previously set up correctly and there has been no outage/hardware swap since, it will probably work fine in spite of this error.)

## 2. Recover Non-Updating EPICS Waveforms



Once in a while, I've seen the EPICS waveform data stop updating. Displays will look like this:



Waveforms frozen

Readback values purple (INVALID)

EPICS-to-RFS communication status OK



If you see this and nothing else seems to be wrong, try pressing 'Halt', then 'Reset' on the appropriate RFS screen. If that does not recover it, then there is a problem somewhere else.

### 3. Ping Test

To test if a chassis pings from a CPU:

- a. Log into LERF workstation or server  
(lcls01/2/3/ lclsapp1 with individual user id)
- b. Log into cpu (using CPU Node Name from Section 1):

iocConsole <cpuname>

OR

ssh laci@<cpuname>

(If prompted for login, type 'laci' and hit enter.)


- c. Type: ping <ip>

### 4. View the EPICS IOC Console

- a. Log into LERF workstation or server  
(lcls01/2/3/lclsapp1 with individual user id)
- b. iocConsole <iocname>
- c. To exit viewer, press these 3 keys together: **Ctrl, a, d**.
- d. To scroll up in viewer, press these 3 keys together: **Ctrl, a, [**. Then use arrows to move up/down. To exit scroll mode, press these 3 keys together: **Ctrl, a, ]**.

(If you inadvertently kill the ioc, you can restart it using the instructions in section 2.)

## 5. Troubleshoot RFS<->Res/Intlk Communication



a. Open Hardware screen. For the appropriate rack, click on an individual chassis

The screenshot shows the 'RF Chassis' interface for 'ACCL:11B:0200:RFS1A'. The 'Comm Diag...' button is circled in orange. The interface is divided into two main sections: 'Chassis Software Controller' and 'Chassis Monitoring'.  
**Chassis Software Controller:**  
 State: Running (with a Reset button)  
 Status: NO\_ALARM  
 Last Error: (empty)  
 Count TX: 3148250  
 Count RX: 3148162  
 Count Timeout: 65  
 Count Error: 0  
 Clock Status: Valid  
 IP Address: 192.168.0.101 (with a Halt button)  
**Chassis Monitoring:**  
 LO: 15.45 dBm  
 Temp: 77.6 DegF (with a More AMC7823... button)  
 QF2 Board 6V: 6.23 V  
 Kintex Temp: 43.12 DegC (with a More FPGA Board... button)  
 QF2 Board Temp: 30.99 DegC  
**Other:**  
 FW Code Hash: a8ecc9403fa2b039138935aa634403b1589e540  
 CRC Errors: 5885, Status: Ok  
 At the bottom, it says 'PRODUCTION' and '01/28/2019 11:56:51'.

b. Click on 'Comm Diag...'



FW Communication Diagnostics - ACCL:LIB:0200 Rack A  
 LLRF Chassis Communication Diagnostics  
 Rack A Cryomodule ACCL:LIB:0200

Exit

### Resonance/Interlock

**Rx 0**

Error Latch			
Link Error			
Timeout			
Wrong Protocol			
CRC Fault			
Wrong Frame			
Protocol Version			
Gateway Type			
Location			

Rev ID: 4F9BA424    Counts: 1719824

**Rx 1**

Error Latch			
Link Error			
Timeout			
Wrong Protocol			
CRC Fault			
Wrong Frame			
Protocol Version			
Gateway Type			
Location			

Rev ID: 4F9BA424    Counts: 13014658

**Tx**

Cav 0 Aux				
Cav 1 Aux				
Cav 2 Aux				
Cav 3 Aux				

Location: 0    0

---

**RFS1**

Error Latch			
Link Error			
Timeout			
Wrong Protocol			
CRC Fault			
Wrong Frame			
Protocol Version			
Gateway Type			
Location			

Rev ID: 4F9BA424    Counts: 13080444

**Tx**

Cav 0 Aux		
Cav 1 Aux		

Location: 0    2

**RFS2**

Error Latch			
Link Error			
Timeout			
Wrong Protocol			
CRC Fault			
Wrong Frame			
Protocol Version			
Gateway Type			
Location			

Rev ID: 4F9BA424    Counts: 13080138

**Tx**

Cav 0 Aux		
Cav 1 Aux		


Location: 0    2

PRODUCTION 01/29/2019 09:58:53

## 6. RF 'Background Process'

Much of the current RF functionality (rack checkout, pulse control, cavity ramp, etc.) is performed by scripts external to the EPICS IOC. This is facilitated by a continuously running background process that is driven by EPICS PVs. This allows us to execute these functions from EPICS PVs on EDM screens—and not have to manually run scripts from the command line.

On every display that relies on this, there is a button titled 'Background process...'. If that process is not running, there will be a red rectangle around it. Click on that button to open a display from which you can start/restart the process. Example:



This process will not successfully launch if the EPICS PVs it relies on are not all online. Both LLRF EPICS IOCs must be on.